

# Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Code: **A0031**  
Product name: **TINTE RAL**  
Chemical name and synonym: **VERNICE ALCHIDICA**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **VERNICE ALCHIDICA IN AEROSOL**

### 1.3. Details of the supplier of the safety data sheet

Name: **Talken Color Srl**  
Full address: **via Don Milani 15**  
District and Country: **20025 Legnano (Mi)**  
**Italia**  
**Tel. 0331/579100**  
**Fax 0331/579372**

e-mail address of the competent person responsible for the Safety Data Sheet: **tecnico@talkencolor.it**

### 1.4. Emergency telephone number

For urgent inquiries refer to: **CENTRO ANTIVELENI dl Milano-Niguarda Tel 0266101029**

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

#### Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words:                    Danger

Hazard statements:

- H222**                                Extremely flammable aerosol.
- H229**                                Pressurised container: may burst if heated.
- H319**                                Causes serious eye irritation.
- H315**                                Causes skin irritation.
- H336**                                May cause drowsiness or dizziness.

Precautionary statements:

- P210**                                Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251**                                Do not pierce or burn, even after use.
- P410+P412**                        Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
- P501**                                Dispose of contents in different containers for steel
- P102**                                Keep out of reach of children.
- P101**                                If medical advice is needed, have product container or label at hand.
- P211**                                Do not spray on an open flame or other ignition source.

**Contains:**                        ACETONE  
    PROPAN-2-OL  
    BUTAN-1-OL  
    N-BUTYL ACETATE

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

## A0031 - TINTE RAL

Contains:

Identification	Conc. %	Classification (EC) 1272/2008 (CLP)
<b>ACETONE</b>		
INDEX 606-001-00-8	31,511	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
EC 200-662-2		
CAS 67-64-1		
REACH Reg. 01-2119471330-49-XXXX		
<b>2-BUTOXYETHANOL</b>		
INDEX 603-014-00-0	2,768	Acute Tox. 3 H331, Acute Tox. 4 H302, Eye Irrit. 2 H319, Skin Irrit. 2 H315
EC 203-905-0		LD50 Oral: 1200 mg/kg, STA Inhalation mists/powders: 0,501 mg/l
CAS 111-76-2		
REACH Reg. 01-2119475108-36-XXXX		
<b>DIACETONE ALCOHOL</b>		
INDEX 603-016-00-1	2,684	Flam. Liq. 3 H226, Eye Irrit. 2 H319, STOT SE 3 H335
EC 204-626-7		
CAS 123-42-2		
REACH Reg. 01-2119473975-21		
<b>XYLENE</b>		
INDEX 601-022-00-9	1,926	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		STA Dermal: 1100 mg/kg, STA Inhalation mists/powders: 1,5 mg/l
CAS 1330-20-7		
REACH Reg. 01-2119488216-32-XXX		
<b>PROPAN-2-OL</b>		
INDEX 603-117-00-0	1,761	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
CAS 67-63-0		
REACH Reg. 01-2119457558-25		
<b>BUTAN-1-OL</b>		
INDEX 603-004-00-6	1,505	Flam. Liq. 3 H226, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, STOT SE 3 H336
EC 200-751-6		LD50 Oral: 790 mg/kg
CAS 71-36-3		
REACH Reg. 01-2119484630-38		
<b>N-BUTYL ACETATE</b>		
INDEX 607-025-00-1	0,548	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
CAS 123-86-4		
REACH Reg. 01-2119485493-29		
<b>ETHYLBENZENE</b>		
INDEX 601-023-00-4	0,239	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Aquatic Chronic 3 H412
EC 202-849-4		STA Inhalation mists/powders: 1,5 mg/l
CAS 100-41-4		

REACH Reg. 01-2119489370-35-XXX

**2-METHOXY-1-METHYLETHYL ACETATE**

INDEX 607-195-00-7 0,043 Flam. Liq. 3 H226

EC 203-603-9

CAS 108-65-6

**TOLUENE**

INDEX 601-021-00-3 0,00064 Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336, Aquatic Chronic 3 H412

EC 203-625-9

CAS 108-88-3

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 46,00 %

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

### 5.2. Special hazards arising from the substance or mixture

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

### 6.2. Environmental precautions

Do not disperse in the environment.

### 6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

#### 2-METHOXY-1-METHYLETHYL ACETATE

Store in an inert atmosphere, sheltered from moisture because it hydrolyses easily.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

# Talken Color Srl

Revision nr. 13

Dated 12/12/2023

## A0031 - TINTE RAL

Printed on 16/01/2024

Page n. 6/21

Replaced revision:12 (Dated: 24/01/2023)

**Regulatory references:**

ESP	España	Límites de exposición profesional para agentes químicos en España 2023
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

### ACETONE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	1210	500			
VLEP	ITA	1210	500			
WEL	GBR	1210	500	3620	1500	
OEL	EU	1210	500			
TLV-ACGIH			250		500	

### 2-BUTOXYETHANOL

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	98	20	245	50	SKIN
VLEP	ITA	98	20	246	50	SKIN
WEL	GBR	123	25	246	50	SKIN
OEL	EU	98	20	246	50	SKIN
TLV-ACGIH		97	20			

### DIACETONE ALCOHOL

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	241	50			
WEL	GBR	241	50	362	75	
TLV-ACGIH		238	50			

### XYLENE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

# Talken Color Srl

Revision nr. 13

Dated 12/12/2023

## A0031 - TINTE RAL

Printed on 16/01/2024

Page n. 7/21

Replaced revision:12 (Dated: 24/01/2023)

### PROPAN-2-OL

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	500	200	1000	400	
WEL	GBR	999	400	1250	500	
TLV-ACGIH		492	200	983	400	

### BUTAN-1-OL

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	61	20	154	50	
WEL	GBR			154	50	SKIN
TLV-ACGIH		61	20			

### N-BUTYL ACETATE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	241	50	723	150	
VLEP	ITA	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

### ETHYLBENZENE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	441	100	884	200	SKIN
VLEP	ITA	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

### 2-METHOXY-1-METHYLETHYL ACETATE

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN

### TOLUENE

# Talken Color Srl

Revision nr. 13

Dated 12/12/2023

## A0031 - TINTE RAL

Printed on 16/01/2024

Page n. 8/21

Replaced revision:12 (Dated: 24/01/2023)

### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH			20			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

None required.

#### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

#### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	aerosol	
Colour	as showed in color folder	
Odour	carratteristico	
Melting point / freezing point	not available	
Initial boiling point	not applicable	
Flammability	non applicabile per aerosol	



Lower explosive limit	not available
Upper explosive limit	not available
Flash point	not applicable
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	not available
Kinematic viscosity	not available
Solubility	solubile in acetone e/o diluente nitro
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	0,738
Relative vapour density	not available
Particle characteristics	not applicable

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Information not available

### 9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	89,41 % - 659,86 g/litre
Explosive properties	durante l'uso puo' formare con l'aria miscele esplosive o infiammabili
Oxidising properties	not applicable
punto di infiammabilità	<0°C
densità relativa (peso specifico)	0,900

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### ACETONE

Decomposes under the effect of heat.

#### 2-BUTOXYETHANOL

Decomposes under the effect of heat.

#### DIACETONE ALCOHOL

Decomposes at temperatures above 90°C/194°F.

#### BUTAN-1-OL

Attacks various types of plastic materials.

#### N-BUTYL ACETATE

Decomposes on contact with: water.

#### 2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

#### TOLUENE

Avoid exposure to: light.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### ACETONE

Risk of explosion on contact with: bromine trifluoride,fluorine dioxide,hydrogen peroxide,nitrosyl chloride,2-methyl-1,3 butadiene,nitromethane,nitrosyl perchlorate.May react dangerously with: potassium tert-butoxide,alkaline hydroxides,bromine,bromoform,isoprene,sodium,sulphur dioxide,chromium trioxide,chromyl chloride,nitric acid,chloroform,peroxymonosulphuric acid,phosphoryl oxychloride,chromosulphuric acid,fluorine,strong oxidising agents,strong reducing agents.Develops flammable gas on contact with: nitrosyl perchlorate.

#### 2-BUTOXYETHANOL

May react dangerously with: aluminium,oxidising agents.Forms peroxides with: air.

#### DIACETONE ALCOHOL

Risk of explosion on contact with: air,sources of heat.May react dangerously with: alkaline metals,amines,oxidising agents,acids.

#### XYLENE

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

#### BUTAN-1-OL

Reacts violently developing heat on contact with: aluminium,strong oxidising agents,strong reducing agents,hydrochloric acid.Forms explosive mixtures with: air.

#### N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

## ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

## 2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

## TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

**10.4. Conditions to avoid**

Avoid overheating.

## ACETONE

Avoid exposure to: sources of heat, naked flames.

## 2-BUTOXYETHANOL

Avoid exposure to: sources of heat, naked flames.

## DIACETONE ALCOHOL

Avoid exposure to: light, sources of heat, naked flames.

## BUTAN-1-OL

Avoid exposure to: sources of heat, naked flames.

## N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

## ACETONE

Incompatible with: acids, oxidising substances.

## N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

## 2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

**10.6. Hazardous decomposition products**

ACETONE

May develop: ketenes, irritant substances.

2-BUTOXYETHANOL

May develop: hydrogen.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

DIACETONE ALCOHOL

WORKERS: inhalation; contact with the skin.

XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

DIACETONE ALCOHOL

Acute toxicity causes irritation of the eyes, nose and throat in humans at 100 ppm (476 mg/kg) and pulmonary disorders at 400 ppm. No chronic effects on humans have been reported. The substance may have a depressive effect on the respiratory centres and cause death from respiratory failure.

XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

#### N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

#### ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

#### 2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

#### TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

#### Interactive effects

#### XYLENE

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

#### N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

#### TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY ATE (Inhalation - mists / powders) of the mixture: > 5 mg/l

ATE (Oral) of the mixture: >2000 mg/kg  
ATE (Dermal) of the mixture: >2000 mg/kg

#### 2-BUTOXYETHANOL

LD50 (Oral): 1200 mg/kg Guinea pig  
LC50 (Inhalation vapours): 3 mg/l/4h Rat  
STA (Inhalation mists/powders): 0,501 mg/l  
(figure used for calculation of the acute toxicity estimate of the mixture)

#### DIACETONE ALCOHOL

LD50 (Oral): 4000 mg/kg Rat

#### XYLENE

LD50 (Dermal): 4350 mg/kg Rabbit  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)  
LD50 (Oral): 3523 mg/kg Rat  
LC50 (Inhalation vapours): 26 mg/l/4h Rat  
STA (Inhalation mists/powders): 1,5 mg/l  
(figure used for calculation of the acute toxicity estimate of the mixture)

## PROPAN-2-OL

LD50 (Dermal):	12800 mg/kg Rat
LD50 (Oral):	4710 mg/kg Rat
LC50 (Inhalation vapours):	72,6 mg/l/4h Rat

## BUTAN-1-OL

LD50 (Dermal):	3400 mg/kg Rabbit
LD50 (Oral):	790 mg/kg Rat
LC50 (Inhalation vapours):	8000 ppm/4h Rat

## N-BUTYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rabbit
LD50 (Oral):	> 6400 mg/kg Rat
LC50 (Inhalation vapours):	21,1 mg/l/4h Rat

## ETHYLBENZENE

LD50 (Dermal):	15354 mg/kg Rabbit
LD50 (Oral):	3500 mg/kg Rat
LC50 (Inhalation vapours):	17,2 mg/l/4h Rat

## 2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Dermal):	> 5000 mg/kg Rat
LD50 (Oral):	8530 mg/kg Rat

## TOLUENE

LD50 (Dermal):	12124 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	28,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

## XYLENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).  
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

## ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).  
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

## TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999). The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Excluded because the aerosol does not allow the accumulation of a significant amount of product in the mouth

#### **11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

## **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

#### **12.1. Toxicity**

Information not available

#### **12.2. Persistence and degradability**

##### XYLENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

##### 2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water > 10000 mg/l

Rapidly degradable

##### TOLUENE

Solubility in water 100 - 1000 mg/l

Rapidly degradable

##### ETHYLBENZENE

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

##### BUTAN-1-OL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

##### 2-BUTOXYETHANOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

## DIACETONE ALCOHOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable  
PROPAN-2-OLRapidly degradable  
ACETONERapidly degradable  
N-BUTYL ACETATE

Solubility in water 1000 - 10000 mg/l

**12.3. Bioaccumulative potential**

## XYLENE

Partition coefficient: n-octanol/water 3,12

BCF 25,9

## 2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1,2

## TOLUENE

Partition coefficient: n-octanol/water 2,73

BCF 90

## ETHYLBENZENE

Partition coefficient: n-octanol/water 3,6

## BUTAN-1-OL

Partition coefficient: n-octanol/water 1

BCF 3,16

## 2-BUTOXYETHANOL

Partition coefficient: n-octanol/water 0,81

## DIACETONE ALCOHOL

Partition coefficient: n-octanol/water -0,09

## PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

## ACETONE

Partition coefficient: n-octanol/water -0,23

BCF 3

## N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2,3

BCF 15,3



**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

**12.7. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information****14.1. UN number or ID number**

ADR / RID, IMDG, IATA: UN 1950

**14.2. UN proper shipping name**

ADR / RID: AEROSOLS, FLAMMABLE

IMDG: AEROSOLS

IATA: AEROSOLS, FLAMMABLE

**14.3. Transport hazard class(es)**

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1

**14.4. Packing group**

ADR / RID, IMDG, IATA: -

**14.5. Environmental hazards**

ADR / RID: NO  
 IMDG: NO  
 IATA: NO

**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special provision: 190, 327, 344, 625		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Passengers:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special provision:	A145, A167, A802	

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Contained substance

Point 75

Point 46a ETHOXYLATED NONYL PHENOL

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

## Regulated explosives precursor

The acquisition, introduction, possession or use of that regulated explosives precursor by members of the general public is subject to reporting obligations as set out in Article 9.

All suspicious transactions and significant disappearances and thefts must be reported to the relevant national contact point.

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2

<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H226</b>	Flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H331</b>	Toxic if inhaled.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H412</b>	Harmful to aquatic life with long lasting effects.
<b>EUH066</b>	Repeated exposure may cause skin dryness or cracking.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 07 / 08 / 12 / 14 / 16.