



TALKEN COLOR S.R.L.  
 Sede e stabilimento:  
 20025 Legnano (Mi) - Via Don Milani, 15  
 Tel. 0331.579100 r.a. - Fax 0331.579372  
 Mecc. 9720178  
 Email: info@talkencolor.it  
 www.talkencolor.it

Reg. Imprese di Milano  
 Società n. 04614930156  
 P. Iva / C.F. 04614930156  
 Cod. ISO/IVA IT 04614930156  
 Cap. Soc. € 10.400,00 i.v.

### TECNICAL DATA SHEET

code	A0031
name	TINTE DI SERIE
nature	VERNICE ALCHIDICA
Nominal Content	520 mL
Net Content	400 mL

### PHYSICAL CHEMICAL CHARACTERISTICS

PHISICAL STATE	LIQUID PIGMENT
CHEMICAL COMPLEXION	SWIFT DRYING ALKYD PAINT
SOLUBILITY	WATER INSOLUBLE
DRYNESS	WITHOUT DUST:SENSE OF TOUCH WITHIN 10 MINUTES.DEEP DRYING WITHIN 6 HOURS
RESISTANCE	AT LIGHT NO TONE VARIATION IN TIME NO RESINS YELLOWING AT ENGINE OILS, CLEANSINGS & PETROL

**PRODUCT DESCRIPTION :** This product meets to need for the industry to have a standard colour chart. TINTE RAL can be over-coated and is suitable for most paintes available on the market. It dries out in 10 minutes and can be used on IRON, ALUMINIUM, GLASS, PLASTICS AND WOOD. It is resistant to petrol.

**TECHNICAL FEATURE:** high surface hardness, high resistance to scratches & bumps & peelings high adhesion to supports. Best covering

**USES:** paintings & refinements for industrial components. colours refer to German Ral Institute

**SUPPORTS:** iron, aluminum, steel, glass, plastic, wood etc.

**HOW TO USE IT:** sand down the support using n°400 sandpaper. Clean up the surface using alcohol. Turn the can upside and shake it for one minute approximately; spray a couple of times empty. These procedures are really important in order to get the real colour. Spray the paint holding the can at close range (approximately cm. 30). avoid leaking spraying both undercoat & topcoat. untreated metal: we recommend you to undercoat our product "areosol rust preserver" plastic: we recommend you to undercoat our product "areosol plastic primer"

**STORAGE: KEEP DRY. DO NOT KEEP UNDER DIRECT SUNSHINE OR ANY OTHER HOTNESS**