



TALKEN COLOR S.R.L.
Sede e stabilimento:
20025 Legnano (Mi) - Via Don Milani, 15
Tel. 0331.579100 r.a. - Fax 0331.579372
Mecc. 9720178
Email: info@talkencolor.it
www.talkencolor.it

Reg. Imprese di Milano
Società n. 04614930156
P. Iva / C.F. 04614930156
Cod. ISO/IVA IT 04614930156
Cap. Soc. € 10.400,00 i.v.

Revised March 4, 2021

TECNICAL DATA SHEET

Code	A0043
Name	Ral color
Nature	ACRYLIC PAINT IN THE ORIGINAL EUROPEAN COLORS
Nominal Content	520 mL
Net Content	400 mL

PHYSICAL CHEMICAL CHARACTERISTICS

PHISICAL STATE	LIQUID PIGMENT
CHEMICAL COMPLEXION	SWIFT DRYING ACRYLIC PAINT
SOLUBILITY	WATER INSOLUBLE
DRYNESS	WITHOUT DUST:SENSE OF TOUCH WITHIN 10 MINUTES.DEEP DRYING WITHIN 24 HOURS
RESISTANCE	AT LIGHT NO TONE VARIATION IN TIME NO RESINS YELLOING AT ENGINE OILS, CLEANINGS & PETROL

PRODUCT DESCRIPTION : RAL COLOR , ACRYLIC PAINT is a modern product, created by following the Ral standard.

This item is a product which particularly fits the industry needs.

The chemical formula is the result of a deep chemical research.

It's a product that also fits the bricolage area for the little jobs in everyone's home.

TECHNICAL SPECIFICATION:

High resistant surface

Scratch/bump proof

High grip

High coverage

It can be overpainted

SUPPORTS: iron, aluminum, glass, plastic, wood , still etc.

HOW TO USE IT: sand down the support using n°400 sandpaper. Clean up the surface using alcohol. Turn the can upside and shake it for one minute approximately; spray a couple of times empty. These procedures are really important in order to get the real colour. Spray the paint holding the can at close range (approximately cm. 30).

avoid leaking spraying both undercoat & topcoat.

untreated metal: we recommend you to undercoat our product "areosol rust preserver" (A0443 -9041) PRIMER PER METALLI

plastic: we recommend you to undercoat our product "areosol plastic primer" (A0443-9040) PRIMER PER PLASTICA

STORAGE: KEEP DRY. DO NOT KEEP UNDER DIRECT SUNSHINE OR ANY OTHER HOTNESS

Le suindicate informazioni tecniche sono basate sulle ns. attuali conoscenze: pertanto al cliente utilizzatore è data la responsabilità di effettuare sempre i propri controlli al fine di valutare i risultati per gli impieghi da esso previsti.

La Talken Color srl si solleva da eventuali responsabilità per applicazioni in modo non conforme alle raccomandazioni di impiego.